


QUCS-S - a central tool in the openPDK IC design flow

Mike Brinson
Centre for Communications Technology
London Metropolitan University, UK
brinsonm@londonmet.ac.uk

Outline


- Qucs-S structure and features
- Qucs-S/IHP Open-PDK file layout
- Example model symbols
- RC, diode and MOS performance test benches
- MOS corner simulation
- DC and AC Monte Carlo analysis
- Analog and digital simulation examples
- XSPICE digital simulation
- QucsRF Octave/openEMF microstrip simulation
- Summary
- Acknowledgments and FOSS links

Qucs-S structure and features



- Red boxes: device and open source PDK data
- Blue boxes: Free and open source circuit simulation software (FOSS)
- Brown boxes: Simulation output data

Qucs-S/IHP Open-PDK file layout




```

.spiceinit x
*
* Qucs-S/Ngspice global initialization file.
* This file must be copied to directory /home/$USER.
* It is read after Ngspice spinit file and prior to passing an Ngspice netlist.
* NOTE: 1. File ".spiceinit" is an Ngspice user defined initialisation file that works with the Linux operating systems.
*        2. Parameter $USER is replaced by the "user name of the computer running Qucs-S. It is unique for each computer.
*           It is determined by Ngspice during initialisation.
*        3. Using parameter $USER removes the need for absolute addressing.
*        4. The Qucs-S/IHP PDK port assumes that projects and associated data can be found at location /home/$USER/.qucs,
*           for example /home/mike/.qucs where $USER is name mike.
*        5. See Qucs-S drop down menu "Applications settings" -> Locations -> Qucs Home: /home/mike/.qucs. The name mike
*           will be different for different computers
*
* Author Mike Brinson: R1 July 2024.
*****
setcs sourcepath = ( $sourcepath /home/$USER/.qucs/IHP-Open-PDK-dev/ihp-sg13g2/libs.tech/ngspice/models )
setcs sourcepath = ( $sourcepath /home/$USER/.qucs/IHP-Open-PDK-dev/ihp-sg13g2/libs.ref/sg13g2_stdcell/spice )
*
*load psp103_nqs.osdi as a global item so that it becomes available to an entire Ngspice netlist.


osdi /home/$USER/.qucs/pspnqs103va.osdi
  
```

Example model symbols



□ Analog devices



□ Example digital standard cells




RC circuit simulation



- ❑ PDK model symbols colored red
- ❑ PDK resistors - name: rxxxx, value: .lib cornerRES.lib res_typ
- ❑ PDK capacitors - names: cmim and rfcim, value: .lib cornerCap.lib cap_typ
- ❑ Other model symbols and simulation command ICONS - Qucs-S

Diode model simulation





Parameter sweep

SW1
 Sim=DC1
 Type=lin
 Param=V1
 Start=0
 Stop=1.2
 Points=2001




dc simulation

DC1
 .INCLUDE SCRIPT
 INCLSCR1
 SpiceCode=
 .INCLUDE diodes.lib



- No "Corner" values for IHP 130nm PDK diodes
- Ngspice .INCLUDE diodes.lib accesses IHP 130nm PDK diode parameters

MOS device dc simulation



- Left figure: nMOS output characteristic test bench and sg13_lv_mos data
- Right figure: MOS inverter test bench and performance data

MOS corner simulation

Parameter sweep



SW1
Sim=DC1
Type=lin
Param=V2
Start=0.1
Stop=1.2
Points=1101

dc simulation



DC1

.INCLUDE SCRIPT
INCLSCR1
SpiceCode=
.LIB cornerMOSiv.lib mos_ff

I1
I=50u





Fast n and p:
mos_ff





mos_ff

Typical n and p:
mos_tt



MOS_tt

Slow n and p:
mos_ss




mos_ss

DC Monte Carlo simulation: 1



```

.INCLUDE SCRIPT
INCLSCR1
SpiceCode=
.control
let number_v3 = 0
let nruns = 10
echo "STEP sw1.v3" > spice4qucs.sw1.cir.res
dowhile $&number_v3 le $&nruns
  reset
  alter v3 = $&number_v3
  dc v2 0.1 1.2 0.01
  let RatioError = 100.0*( 1.0 - (i(vpout))/( i(vpIn)+1e-12 ) )
  write spice4qucs.sw1._swp.plot i(VPin) i(VPout) v(n1) RatioError
  set appendwrite
  echo "$&number_v3" >> spice4qucs.sw1.cir.res
  let number_v3 =number_v3 + 1
end
unset appendwrite
destroy all
reset
exit
.endc
.end
    
```



```







.INCLUDE SCRIPT
INCLSCR2
SpiceCode=
.PARAM mc_ok = 1.0
.LIB cornerMOSlv.lib mos_ft_stat
*
    
```



DC Monte Carlo simulation: 2

```


.INCLUDE SCRIPT
INCLSCR5
SpiceCode=
.control
let number_v3 = 0
let nruns = 100
echo "STEP sw1.v3" > spice4qucs.sw1.cir.res
dowhile %number_v3 le %nruns
  reset
  alter v3 = %number_v3
  dc v2 1.0 1.1 1.0
  let RatioError = 100.0*( 1.0 - (i(vpout)/( i(vpin)+1e-12 ) ) )
  write spice4qucs.sw1._swp.plot i(VPin) i(VPout) v(n1) RatioError
  set appendwrite
  echo "%number_v3 " >> spice4qucs.sw1.cir.res
  let number_v3 = number_v3 + 1
end
unset appendwrite
destroy all
reset
exit
.endc
.end
    
```



```


% Octave histogram plot.
DataSetFile = "CM_MC_S2_2A.dat.ngspice"
Y1name = "sw1.i(vpout)"
Y1label = "Sample count"
X1label = "i(vpout)"
Y2name = "sw1.ratioerror"
Y2label = "Sample count"
X2label = "RatioError (%)"
nbins = 7
plotHistogram2V(DataSetFile, Y1name, Y1label, X1label, Y2name, Y2label, X2label, nbins)
    
```

AC Monte Carlo simulation: 1



- Dummy component **R2** and parameter **nruns** link Ngspice script and Qucs-s schematics
- Note use of IHP res-typ_stat and cap_wcs_stat libraries

AC Monte Carlo simulation: 2



```
.INCLUDE SCRIPT
INCLSCR8
SpiceCode=
.param mc_ok= 1.0
.lib cornerRES.lib res_typ_stat
.lib cornerCAP.lib cap_wcs_stat
```


```
.INCLUDE SCRIPT
INCLSCR6
SpiceCode=
*
R1 nd1 0 1e9
R2 n1 nd1 1
.control
let number_r2 = 0
let nruns = 1000
echo "STEP sw1.r2" > spice4qucs.ac1.cir.res
dowhile $&number_r2 le $&nruns
reset
alter R2 = $&number_r2
ac lin 1 1e10 10.1e10
write spice4qucs.ac1._swp.plot v(n1) v(n2) v(n3) abs(v(n4))
set appendwrite
echo "$&number_r2 " >> spice4qucs.ac1.cir.res
let number_r2 = number_r2 + 1
end
unset appendwrite
destroy all
reset
exit
.endc
.END
```

Parameter sweep


SW1
Sim=AC1
Param=R2

ac simulation

AC1
Type=const
Values=[10g]




Octave script



- Frequency set at 10GHz
- nruns = 1000

Example sg13g2 hv analog CM blocks



[INCLUDE SCRIPT](#)

INCLSCR1
SpiceCode=
.LIB cornerMOShv.lib mos_tt

Parameter sweep





SW1
Sim=DC1
Type=lin
Param=V2
Start=0.8
Stop=3.0
Points=55

dc simulation


DC1

[Nutmeg](#)

NutmegEq1
Simulation=SW1
rout_wcm=V(nout2)/i(vPr2)
rout_scm=V(nout1)/i(vPr3)




sg13g2 digital stdcell simulation




- Logic 0 = 0.0V and 1 = 1.2V
- Output signals: DLY3_1 = red; DLY3_2 = blue; DLY3_3 = mauve; DLY3_4 = green

Mixed analog and digital simulation



- Qucs-S/Ngspice IHP PDK digital stdcell ring oscillator
- C1, C2 and C3 set to measured values for "mid" size devices

XSPICE digital simulation



- Qucs-S/XSPICE digital stdcell ring oscillator
- Logic levels: 0 = 0.0V, U = 0.6V and 1 = 1.2V

QucsatorRF/openEMF simulation

Qucs-RFLayout

Input : /home/mike/.qucs/RFtestsIHP_prj/testmstrip3.sch

Netlist : /home/mike/.qucs/RFtestsIHP_prj/testmstrip3.net

Write : /home/mike/.qucs/RFtestsIHP_prj/testmstrip3.m

Actions

OpenEMS parameters

High res div : 200

Metal res div : 60

Subst res div : 30

Time res : 300000

End criteria : 1e-4

NF2FF center :

Sort metal res mesh lines

Use Octave packages

General parameters

Whole layout in a file

Each substrate in a file

Each block in a file

Format : .m

Output : /home/mike/.qucs/RFtestsIHP_prj

QucsatorRF

MS1 Subst=Subst1 W=0.6 mm L=30 mm

MS2 Subst=Subst1 W1=0.6 mm W2=0.6 mm W3=0.6 mm L=30 mm

MS3 Subst=Subst1 W=0.6 mm L=30 mm

MS4 Subst=Subst1 W=0.6 mm L=12 mm

MS5 Subst=Subst1 W=0.6 mm

P1 Num=1 Z=50 Ohm


P2 Num=2 Z=50 Ohm

Subst1 er=3.66 h=0.254 mm t=10 um

S parameter simulation

SP1 Type=lin Start=0.1 GHz Stop=7 GHz Points=500

xxx.m



KiCAD

QucsatorRF

Octave

QUCS-S - a central tool in the openPDK IC design flow

Summary

- The recent rapid developments in semiconductor technologies and devices has increased the pressure on circuit design tools to keep in step with user needs. This is particularly true in areas driven by the release of open source analogue, RF and mixed signal PDKs.
- This presentation reports on developments in the latest Qucs-S and Ngspice FOSS tools for IC design using the IHP 130 nm BiCMOS Open Source PDK (sg13g2).
- A series of Qucs-S/Ngspice/IHP PDK simulation test benches outline the application of Free Open Source (FOSS) tools, or equivalent licence software, for IC design.
- All the software tools outlined in this presentation are freely available from the web sites listed on slide 20.
- Future work will concentrate on developing a series of analogue/RF/mixed signal test structures for production by IHP and subsequent performance measurement. This will allow the accuracy of the Qucs-S/Ngspice simulation output data to be checked.

Acknowledgments and FOSS links



The IHP (Leibniz-Institut für innovative Mikroelektronik) Open PDK Development Team (project leader René Scholtz) : <https://github.com/IHP-GmbH/IHP-Open-PDK>,



The Qucs-S (Qucs with SPICE) Development Team, <https://ra3xdh.github.io/> : Qucs-S 24.3.0, 23 July 2024



The Ngspice (next generation open source SPICE) Development Team <https://ngspice.sourceforge.io/> :
ngspice-43_64.7z, 13 July 2024



The openEMS (open electromagnetic field solver) Development Team :
<https://github.com/thliebig/openEMS-Project>, openEMS 0.0.36, 22 October 2023

OpenVAF

The openVAF (next-Generation Verilog-A compiler) Development Team <https://openvaf.semimod.de/> :
openVAF with noise support (Beta), 1 January 2024